

COMPRESSOR DATA SHEET

**In Accordance With Federal Uniform Test Method for Certain Lubricated Air Compressors
Rotary Compressor: Variable Frequency Drive**

MODEL DATA - FOR COMPRESSED AIR

| | | | |
|----|--|--------------------------------|---|
| 1 | Manufacturer: Hertz Kompressoren | | |
| 2 | Model Number: HVD 75 | Date: | 05.07.21 |
| | <input checked="" type="checkbox"/> Air-cooled <input type="checkbox"/> Water-cooled | Type: | Screw |
| | <input checked="" type="checkbox"/> Oil-injected <input type="checkbox"/> Oil-free | # of Stages: | 1 |
| 3 | Rated Operating Pressure | 125 | psig ^b |
| 4 | Drive Motor Nominal Rating | 100 | hp |
| 5 | Drive Motor Nominal Efficiency | 95,6 | percent |
| 6 | Fan Motor Nominal Rating (if applicable) | 3,89 | hp |
| 7 | Fan Motor Nominal Efficiency | 82,6 | percent |
| 8* | Input Power (kW) | Capacity (acfm) ^{a,d} | Specific Power (kW/100 acfm) ^d |
| | 94,5 Max | 437,9 | 21,58 |
| | 82,7 | 382,2 | 21,64 |
| | 70,4 | 325,7 | 21,61 |
| | 59,9 | 271,6 | 22,05 |
| | 49,2 | 218,2 | 22,55 |
| | 38,8 Min | 170,5 | 22,76 |
| 9* | Total Package Input Power at Zero Flow ^{c, d} | 13,0 | kW |
| 10 | Isentropic Efficiency | 69,6 | Percent |
| 11 | <p>Note: Graph is only a visual representation of the data in Section 8 Note: Y-Axis Scale, 10 to 35, + 5kW/100acfm increments if necessary above 35 X-Axis Scale, 0 to 25% over maximum capacity</p> | | |

*For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator

Consult CAGI website for a list of participants in the third party verification program: www.cagi.org

NOTES:

- a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E; ACFM is actual cubic feet per minute at inlet conditions.
- b. The operating pressure at which the Capacity (Item 8) and Electrical Consumption (Item 8) were measured for this data sheet.
- c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.
- d. Tolerance is specified in ISO 1217, Annex E, as shown in table below:

NOTE: The terms "power" and "energy" are synonymous for purposes of this document.



Member

| Volume Flow Rate at specified conditions | | Volume Flow Rate | Specific Energy Consumption | No Load / Zero Flow Power |
|--|----------------------------------|------------------|-----------------------------|---------------------------|
| $\frac{\text{m}^3}{\text{min}}$ | $\frac{\text{ft}^3}{\text{min}}$ | % | % | % |
| Below 0.5 | Below 17.6 | +/- 7 | +/- 8 | |
| 0.5 to 1.5 | 17.6 to 53 | +/- 6 | +/- 7 | +/- 10% |
| 1.5 to 15 | 53 to 529.7 | +/- 5 | +/- 6 | |
| Above 15 | Above 529.7 | +/- 4 | +/- 5 | |

ROT 031.1