COMPRESSOR DATA SHEET

In Accordance With Federal Uniform Test Method for Certain Lubricated Air Compressors **Rotary Compressor: Variable Frequency Drive**

1	Manufacturer:	Hertz Kompressoren		
2	Model Number:	IMPETUS VSD 37	Date:	12.18.23
	Air-cooled	X Water-cooled	Type:	Screw
	X Oil-injected	Oil-free	# of Stages:	2
3	Rated Operating Pressure		100	psig ^b
4	Drive Motor Nominal Rating		50	hp
5	Drive Motor Nominal Efficiency		96,1	percent
6	Fan Motor Nominal Rating (if applicable)		N/A	hp
7	Fan Motor Nominal Effi	ciency	N/A	percent
8*	Input Po	wer (kW)	Capacity (acfm) ^{a,d}	Specific Power (kW/100 acfm)
	43,9	Max	271,2	16,20
	36,7		232,4	15,79
	30,0		188,6	15,92
	23,9		146,9	16,24
	18,0		105,6	17,08
	12,2 Min		62,5	19,48
9*	Total Package Input Power at Zero Flow ^{c, d}		5,6	kW
10	Isentropic Efficiency		82,1	Percent
11	30,00 25,00 25,00 20,00 20,00 15,00			
	10,00	Note: Graph is only a visual rep Note: Y-Axis Scale, 10 to 35, + 5kW/i	200 y (ACFM) resentation of the data in Section 100acfm increments if necessary ab- 6 over maximum capacity	

or Consult CAGI website for a list of participants in the third party verification program: www.cagi.org NOTES:

- a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E;
 - ACFM is actual cubic feet per minute at inlet conditions.
 - b. The operating pressure at which the Capacity (Item 8) and Electrical Consumption (Item 8) were measured for this data sheet. c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%,

Compressed Air & Gas Institute

Member

manufacturer may state "not significant" or "0" on the test report. d. Tolerance is specified in ISO 1217, Annex E, as shown in table below:

NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

Volume Flow Rate Specific Energy at specified conditions Volume Flow Rate Consumption No Load / Zero Flow Power ft³ / min % m^3 / min % % Below 17.6 Below 0.5 +/- 7 +/- 8 17.6 to 53 +/- 7 0.5 to 1.5 +/- 6 +/- 10% 53 to 529.7 1.5 to 15 +/- 5 +/- 6 Above 529.7 ROT 031.1 Above 15 +/- 4 +/- 5

2/19 Rev 3 This form was developed by the Compressed Air and Gas Institute for the use of its members participating in the PVP. CAGI has not independently verified the reported data.