

COMPRESSOR DATA SHEET

In Accordance With Federal Uniform Test Method for Certain Lubricated Air Compressors **Rotary Compressor: Variable Frequency Drive**

Manufacturer: Hertz Kompressoren Model Number: IMPETUS VSD 75 Air-cooled X Water-cooled X Oil-injected Oil-free Rated Operating Pressure Drive Motor Nominal Rating Drive Motor Nominal Efficiency	Date: Type: # of Stages: 100 100	12.18.23 Screw 2 psig ^b
Air-cooled X Water-cooled X Oil-injected Oil-free Rated Operating Pressure Drive Motor Nominal Rating Drive Motor Nominal Efficiency	Type:	Screw 2
X Oil-injected Oil-free Rated Operating Pressure Drive Motor Nominal Rating Drive Motor Nominal Efficiency	# of Stages: 100 100	2
Rated Operating Pressure Drive Motor Nominal Rating Drive Motor Nominal Efficiency	100 100	
Drive Motor Nominal Rating Drive Motor Nominal Efficiency	100	psig ^b
Drive Motor Nominal Efficiency		
·		hp
	96,9	percent
Fan Motor Nominal Rating (if applicable)	N/A	hp
Fan Motor Nominal Efficiency	N/A	percent
Input Power (kW)	Capacity (acfm) ^{a,d}	Specific Power (kW/100 acfm) ^d
89,1 Max	570,7	15,62
75,0	485,9	15,44
61,5	399,1	15,40
47,3	302,6	15,64
34,3	211,2	16,25
22,7 Min	120,8	18,83
Total Package Input Power at Zero Flow ^{c, d}	7,8	kW
Isentropic Efficiency	85,1	Percent
	•	600
	Input Power (kW) 89,1 Max 75,0 61,5 47,3 34,3 32,7 Min Total Package Input Power at Zero Flow ^{c, d} Isentropic Efficiency 30,00 25,00 15,00 Note: Graph is only a visual rep Note: Y-Axis Scale, 10 to 35, + 5kW/l	Input Power (kW) 89,1 Max 570,7 75,0 485,9 61,5 399,1 47,3 302,6 34,3 211,2 22,7 Min 120,8 Total Package Input Power at Zero Flow ^{c, d} Isentropic Efficiency 85,1

*For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator Consult CAGI website for a list of participants in the third party verification program:

- a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E; ACFM is actual cubic feet per minute at inlet conditions.
- b. The operating pressure at which the Capacity (Item 8) and Electrical Consumption (Item 8) were measured for this data sheet.
- c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.
- d. Tolerance is specified in ISO 1217, Annex E, as shown in table below:

NOTE: The terms "power" and "energy" are synonymous for purposes of this document.



Member					
	Volume Flow Rate			Specific Energy	
	at specified conditions		Volume Flow Rate	Consumption	No Load / Zero Flow Power
	m ³ /min	ft ³ / min	%	%	%
	Below 0.5	Below 17.6	+/- 7	+/- 8	
	0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	+/- 10%
	1.5 to 15	53 to 529.7	+/- 5	+/- 6	+/- 1070
ROT 031.1	Above 15	Above 529.7	+/- 4	+/- 5	
12/19 Rev 3 This form was developed by the Compressed Air and Gas Institute for the use of its members participating in the PVP. CAGI has not independently verified the reported data.					