

COMPRESSOR DATA SHEET

In Accordance with Federal Uniform Test Method for Certain Lubricated Air Compressors

Rotary Compressor: Fixed Speed

MODEL DATA - FOR COMPRESSED AIR			
1	Manufacturer: Hertz Kompressoren		
	Model Number: IMPETUS 110	Date:	09.16.22
2	X Air-cooled Water-cooled	Type:	Screw
	X Oil-injected Oil-free	# of Stages:	2
	Rated Capacity at Full Load Operating		
3*	Pressure ^{a, e}	789,6	acfm ^{a,e}
4	Full Load Operating Pressure ^b	100	psig ^b
5	Maximum Full Flow Operating Pressure ^c	100	psig ^c
6	Drive Motor Nominal Rating	150	hp
7	Drive Motor Nominal Efficiency	96,5	percent
8	Fan Motor Nominal Rating (if applicable)	3 / 2	hp
9	Fan Motor Nominal Efficiency	84 / 83	percent
10*	Total Package Input Power at Zero Flow ^e	54,4	kW ^e
11	Total Package Input Power at Rated Capacity and Full Load Operating Pressure ^d	129,3	kW^d
12*	Specific Package Input Power at Rated Capacity and Full Load Operating Pressure ^e	16,37	kW/100 cfm ^e
13	Isentropic Efficiency	81,2	Percent

*For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator. Consult CAGI website for a list of participants in the third party verification program: <u>www.cagi.org</u>

NOTES:

- a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex C; ACFM is actual cubic feet per minute at inlet conditions.
- b. The operating pressure at which the Capacity (Item 3) and Electrical Consumption (Item 11) were measured
 - for this data sheet.c. Maximum pressure attainable at full flow, usually the unload pressure setting for load/no load control or the maximum pressure attainable before capacity control begins. May require additional power.

d. Total package input power at other than reported operating points will vary with control strategy.



ROT 030.1

e. Tolerance is specified in ISO 1217, Annex C, as shown in table below: NOTE: The terms "power" and "energy" are synonymous for purposes of this document. Volume Flow Rate No Load / Zero Flow at specified conditions Volume Flow Rate Specific Energy Consumption Power m³/min % % <u>ft3 / min</u> Below 0.5 +/- 7 +/- 8 Below 17.6 0.5 to 1.5 +/- 7 +/- 6 +/- 10% 17.6 to 53 1.5 to 15 +/- 5 +/- 6 53 to 529.7 Above 15 Above 529.7 +/- 4 +/- 5

12/19 Rev 3 This form was developed by the Compressed Air and Gas Institute for the use of its members participating in the PVP. CAGI has not independently verified the reported data.