

COMPRESSOR DATA SHEET
Rotary Compressor: Fixed Speed

MODEL DATA - FOR COMPRESSED AIR

| | | | | |
|-----|--|--|-------------------------|------------------|
| 1 | Manufacturer: | Hertz Kompressoren | | |
| 2 | Model Number: | IMPETUS 185 | Date: | 4/26/2023 |
| | <input type="checkbox"/> Air-cooled | <input checked="" type="checkbox"/> Water-cooled | Type: | Screw |
| | <input checked="" type="checkbox"/> Oil-injected | <input type="checkbox"/> Oil-free | # of Stages: | 2 |
| 3* | Rated Capacity at Full Load Operating Pressure ^{a, e} | 1261.8 | acfm ^{a, e} | |
| 4 | Full Load Operating Pressure ^b | 100 | psig ^b | |
| 5 | Maximum Full Flow Operating Pressure ^c | 100 | psig ^c | |
| 6 | Drive Motor Nominal Rating | 250 | hp | |
| 7 | Drive Motor Nominal Efficiency | 96.7 | percent | |
| 8 | Fan Motor Nominal Rating (if applicable) | N/A | hp | |
| 9 | Fan Motor Nominal Efficiency | N/A | percent | |
| 10* | Total Package Input Power at Zero Flow ^e | 82.3 | kW ^e | |
| 11 | Total Package Input Power at Rated Capacity and Full Load Operating Pressure ^d | 203.6 | kW ^d | |
| 12* | Specific Package Input Power at Rated Capacity and Full Load Operating Pressure ^e | 16.1 | kW/100 cfm ^e | |

*For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator. Consult CAGI website for a list of participants in the third party verification program: www.cagi.org

- NOTES:
- Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex C; ACFM is actual cubic feet per minute at inlet conditions.
 - The operating pressure at which the Capacity (Item 3) and Electrical Consumption (Item 11) were measured for this data sheet.
 - Maximum pressure attainable at full flow, usually the unload pressure setting for load/no load control or the maximum pressure attainable before capacity control begins. May require additional power.
 - Total package input power at other than reported operating points will vary with control strategy.
 - Tolerance is specified in ISO 1217, Annex C, as shown in table below:

Member



| Volume Flow Rate at specified conditions | | Volume Flow Rate | Specific Energy Consumption | No Load / Zero Flow Power |
|--|-----------------------|------------------|-----------------------------|---------------------------|
| m ³ / min | ft ³ / min | % | % | |
| Below 0.5 | Below 15 | +/- 7 | +/- 8 | +/- 10% |
| 0.5 to 1.5 | 15 to 50 | +/- 6 | +/- 7 | |
| 1.5 to 15 | 50 to 500 | +/- 5 | +/- 6 | |
| Above 15 | Above 500 | +/- 4 | +/- 5 | |

ROT 030