

## **COMPRESSOR DATA SHEET**

In Accordance with Federal Uniform Test Method for Certain Lubricated Air Compressors **Rotary Compressor: Fixed Speed** 

MODEL DATA - FOR COMPRESSED AIR							
1	Manufacturer: Hertz Kompressoren						
	Model Number: IMPETUS 200	Date:	09.16.22				
2	X Air-cooled Water-cooled	Type:	Screw				
	X Oil-injected Oil-free	# of Stages:	2				
	Rated Capacity at Full Load Operating						
3*	Pressure a, e	1077,1	acfm <sup>a,e</sup>				
4	Full Load Operating Pressure b	175	psig b				
5	Maximum Full Flow Operating Pressure <sup>c</sup>	175	psig <sup>c</sup>				
6	Drive Motor Nominal Rating	270	hp				
7	Drive Motor Nominal Efficiency	96,7	percent				
8	Fan Motor Nominal Rating (if applicable)	7/3	hp				
9	Fan Motor Nominal Efficiency	88 / 84	percent				
10*	Total Package Input Power at Zero Flow	122	kW <sup>e</sup>				
11	Total Package Input Power at Rated Capacity and Full Load Operating Pressure <sup>d</sup>	250,6	$kW^d$				
12*	Specific Package Input Power at Rated  Capacity and Full Load Operating Pressure	23,27	kW/100 cfm <sup>e</sup>				
13	Isentropic Efficiency	77,0	Percent				

NOTES:

- a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex C; ACFM is actual cubic feet per minute at inlet conditions.
- b. The operating pressure at which the Capacity (Item 3) and Electrical Consumption (Item 11) were measured for this data sheet.
- c. Maximum pressure attainable at full flow, usually the unload pressure setting for load/no load control or the
  maximum pressure attainable before capacity control begins. May require additional power.
- d. Total package input power at other than reported operating points will vary with control strategy.
- e. Tolerance is specified in ISO 1217, Annex C, as shown in table below:

NOTE: The terms "power" and "energy" are synonymous for purposes of this document.



Member

ROT 030.1

	Volume Flow Rate at specified conditions		Volume Flow Rate	Specific Energy Consumption	No Load / Zero Flow Power
Ī	$\underline{\mathbf{m}^3 / \mathbf{min}}$	<u>ft3 / min</u>	%	%	
Ī	Below 0.5	Below 17.6	+/- 7	+/- 8	
	0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	+/- 10%
	1.5 to 15	53 to 529.7	+/- 5	+/- 6	
	Above 15	Above 529.7	+/- 4	+/- 5	

This form was developed by the Compressed Air and Gas Institute for the use of its members participating in the PVP. CAGI has not independently verified the reported data.

<sup>\*</sup>For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator. Consult CAGI website for a list of participants in the third party verification program: