COMPRESSOR DATA SHEET

In Accordance With Federal Uniform Test Method for Certain Lubricated Air Compressors Rotary Compressor: Variable Frequency Drive

1	Manufacturer:	EL DATA - FOR COM	FRESSED AIR	
1		Hertz Kompressoren		
2	Model Number:	IMPETUS VSD 110 X Water-cooled	Date: Type:	04/25/23 Screw
	X Oil-injected	l 🗌 Oil-free	# of Stages:	2
3	Rated Operating Pressu	•		psig ^b
4	Drive Motor Nominal Rating		150	hp
5	Drive Motor Nominal Efficiency		96.5	percent
6	Fan Motor Nominal Rating (if applicable)		N/A	hp
7	Fan Motor Nominal Efficiency		N/A	percent
	Input Power (kW)		Capacity (acfm) ^{a,d}	Specific Power (kW/100 acfm)
	133.9 Max		616.6	21.71
	116.4		542.9	21.45
8*	102.5		468.6	21.88
	86.1		387.0	22.26
	72.7		315.0	23.08
	58.0 Min		230.3	25.19
9*	Total Package Input Po	wer at Zero Flow ^{c, d}	17.2	kW
10	Isentropic Efficiency		82.5	Percent
11	30.00 - 25.00 - (W100 OCEN) 20.00 - 15.00 -			
	10.00 + 0	Capacit Note: Graph is only a visual rep Note: Y-Axis Scale, 10 to 35, + 5kW/1	500 600 700 800 y (ACFM) resentation of the data in Section 00acfm increments if necessary abo 6 over maximum capacity	8

*For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator Consult CAGI website for a list of participants in the third party verification program: www.cagi.org



- a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E; ACFM is actual cubic feet per minute at inlet conditions.
 b. The operating pressure at which the Capacity (Item 8) and Electrical Consumption (Item 8) were measured for this data sheet.
- c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%,
- manufacturer may state "not significant" or "0" on the test report.
- d. Tolerance is specified in ISO 1217, Annex E, as shown in table below:
 - NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

Member

Vo	lume Flow Rate		Specific Energy		
at spo	ecified conditions	Volume Flow Rate	Consumption	No Load / Zero Flow Power	
$\underline{m^3 / \min}$	$\underline{ft^3} / \underline{min}$	%	%	%	
Below 0.5	Below 17.6	+/- 7	+/- 8	+/- 10%	
0.5 to 1.5	17.6 to 53	+/- 6	+/- 7		
1.5 to 15	53 to 529.7	+/- 5	+/- 6		
Above 15	Above 529.7	+/- 4	+/- 5		

ROT 031.1 12/19 Rev 3 This for