

COMPRESSOR DATA SHEET

In Accordance With Federal Uniform Test Method for Certain Lubricated Air Compressors Rotary Compressor: Variable Frequency Drive

MODEL DATA - FOR COMPRESSED AIR						
1 Manufacturer: Hertz Kompressoren						
Model Number: IMPETUS	umber: IMPETUS VSD 132 Date:		04/25/23			
Air-cooled X Wate	Air-cooled X Water-cooled		Screw			
X Oil-injected Oil-fi	Oil-injected Oil-free		2			
Rated Operating Pressure		125	psig ^b			
Drive Motor Nominal Rating		180	hp			
Drive Motor Nominal Efficiency		96.9	percent			
Fan Motor Nominal Rating (if applicable)		N/A	hp			
Fan Motor Nominal Efficiency		N/A	percent			
Input Power (kW)		Capacity (acfm) ^{a,d}	Specific Power (kW/100 acfm) ^d			
169.1	Max	914.6	18.48			
142.1		781.7	18.18			
119.0		662.0	17.97			
95.4		526.7	18.10			
75.1		403.8	18.59			
52.5 Min		269.5	19.49			
Total Package Input Power at Zero Flow ^{c, d}		20.3	kW			
Isentropic Efficiency		81.3	Percent			
Note: Y-Axis So	oh is only a visual rep cale, 10 to 35, + 5kW/	y (ACFM) resentation of the data in Section 00acfm increments if necessary a				
	Model Number: Manufacturer: Model Number: IMPETU Air-cooled X Wate X Oil-injected Oil-fi Rated Operating Pressure Drive Motor Nominal Rating Drive Motor Nominal Efficiency Fan Motor Nominal Efficiency Input Power (kW) 169.1 142.1 119.0 95.4 75.1 52.5 Total Package Input Power at Zero Flot Isentropic Efficiency 30.00 Note: Gray Note: Y-Axis St. Note: Y-Axis	MODEL DATA - FOR COM Manufacturer: Hertz Kompressoren Model Number: IMPETUS VSD 132 Air-cooled X Water-cooled X Oil-injected Oil-free Rated Operating Pressure Drive Motor Nominal Rating Drive Motor Nominal Efficiency Fan Motor Nominal Efficiency Input Power (kW) 169.1 Max 142.1 119.0 95.4 75.1 52.5 Min Total Package Input Power at Zero Flow ^{c, d} Isentropic Efficiency Isentropic Efficiency Note: Graph is only a visual reproductive for sonly a visual repro	MODEL DATA - FOR COMPRESSED AIR Manufacturer: Hertz Kompressoren Model Number: IMPETUS VSD 132 Date:			

^{*}For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator Consult CAGI website for a list of participants in the third party verification program: www.cagi.org

- a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E;
 ACFM is actual cubic feet per minute at inlet conditions.
- b. The operating pressure at which the Capacity (Item 8) and Electrical Consumption (Item 8) were measured for this data sheet.
- c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%,
- manufacturer may state "not significant" or "0" on the test report.
 d. Tolerance is specified in ISO 1217, Annex E, as shown in table below:
- NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

Member

Compressed Air & Gas Institute

Vo	olume Flow Rate		Specific Energy	
at sp	pecified conditions	Volume Flow Rate	Consumption	No Load / Zero Flow Power
$\underline{m}^3 / \underline{min}$	ft ³ / min	%	%	%
Below 0.5	Below 17.6	+/- 7	+/- 8	
0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	+/- 10%
1.5 to 15	53 to 529.7	+/- 5	+/- 6	
Above 15	Above 529.7	+/- 4	+/- 5	

ROT 031.1

12/19 Rev 3 This form was developed by the Compressed Air and Gas Institute for the use of its members participating in the PVP. CAGI has not independently verified the reported data