

COMPRESSOR DATA SHEET

In Accordance With Federal Uniform Test Method for Certain Lubricated Air Compressors Rotary Compressor: Variable Frequency Drive

		MODEL DA										
1	Manufacturer:	Her	tz Kompress	oren								
	Model Number: IMPETUS VSD 132					Date:			04/25/23			
2	Air-c	Air-cooled X Water-cooled				Type:			Screw			
	X Oil-injected Oil-free					# of Stages:			2			
3	Rated Operating	erating Pressure					150			psig ^b		
4	Drive Motor Nor	tor Nominal Rating					180			hp		
5	Drive Motor Nor	tor Nominal Efficiency					96.9			percent		
6	Fan Motor Nomi	or Nominal Rating (if applicable)				N/A			hp			
7	Fan Motor Nomi	otor Nominal Efficiency					N/A			percent		
	Input Power (kW)				Capacity (acfm) ^{a,d}			Specific Power (kW/100 acfm) ^d				
	167.1 Max				834.2			20.03				
O.t.	144.1				729.9			19.74				
8*	119.6				604.5			19.78				
	99.8			499.2			19.98					
	77.4				376.2			20.58				
	58.0 Min			263.4			22.03					
9*	Total Package In	ekage Input Power at Zero Flow ^{c, d}				20.3			kW			
10	Isentropic Efficie	Efficiency			82.6				Percent			
11	Specific Power (kW/100 ACFM)			visual rep		n of the c			900	1000		
		Note: Graph is only a visual representation of the data in Section 8 Note: Y-Axis Scale, 10 to 35, + 5kW/100acfm increments if necessary above 35 X-Axis Scale, 0 to 25% over maximum capacity										

^{*}For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator Consult CAGI website for a list of participants in the third party verification program: www.cagi.org

- e for a list of participants in the third party verification program: www.cagi.org
 a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E;
 ACFM is actual cubic feet per minute at inlet conditions.
- b. The operating pressure at which the Capacity (Item 8) and Electrical Consumption (Item 8) were measured for this data sheet.
- c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%,
- manufacturer may state "not significant" or "0" on the test report.
 d. Tolerance is specified in ISO 1217, Annex E, as shown in table below:
- NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

Member

Compressed Air & Gas Institute

	V	olume Flow Rate		Specific Energy		
	at specified conditions		Volume Flow Rate Consumption		No Load / Zero Flow Power	
<u>m³ / 1</u>	min_	ft ³ / min	%	%	%	
Below	0.5	Below 17.6	+/- 7	+/- 8		
0.5 to	1.5	17.6 to 53	+/- 6	+/- 7	+/- 10%	
1.5 to	15	53 to 529.7	+/- 5	+/- 6	T/- 1070	
Abov	e 15	Above 529.7	+/- 4	+/- 5		

ROT 031.1

12/19 Rev 3 This form was developed by the Compressed Air and Gas Institute for the use of its members participating in the PVP. CAGI has not independently verified the reported data