COMPRESSOR DATA SHEET

In Accordance With Federal Uniform Test Method for Certain Lubricated Air Compressors Rotary Compressor: Variable Frequency Drive

	· · · · ·	EL DATA - FOR COM		
1	Manufacturer:	Hertz Kompressoren		
	Model Number:	IMPETUS VSD 132	Date:	04/25/23
2	Air-cooled	X Water-cooled	Type:	Screw
	X Oil-injected	Oil-free	# of Stages:	2
3	Rated Operating Pressur	·e	175	$psig^{b}$
4	Drive Motor Nominal R	ating	180	hp
5	Drive Motor Nominal E	fficiency	96.9	percent
6	Fan Motor Nominal Rat	ing (if applicable)	N/A	hp
7	Fan Motor Nominal Effi	ciency	N/A	percent
	Input Power (kW)		Capacity (acfm) ^{a,d}	Specific Power (kW/100 acfm) ^d
	163.1 Max		756.3	21.56
8*	141.9		662.6	21.42
8*	122.3		570.5	21.44
	100.9		451.7	22.35
	82.1		357.8	22.95
	63.6 Min		263.0	24.18
9*	Total Package Input Pov	ver at Zero Flow ^{c, d}	20.3	kW
10	Isentropic Efficiency		83.1	Percent
11	30.00 25.00 25.00 20.00 15.00 10.00 0	-	500 600 700 80 y (ACFM) resentation of the data in Section	8

*For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator Consult CAGI website for a list of participants in the third party verification program: www.cagi.org



- a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E; ACFM is actual cubic feet per minute at inlet conditions.b. The operating pressure at which the Capacity (Item 8) and Electrical Consumption (Item 8) were measured for this data sheet.
- c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%,
- manufacturer may state "not significant" or "0" on the test report.
- d. Tolerance is specified in ISO 1217, Annex E, as shown in table below:
 - NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

Member

Volume Flow Rate			Specific Energy	
at spec	cified conditions	Volume Flow Rate	Consumption	No Load / Zero Flow Power
$\underline{m^3 / \min}$	<u>ft³ / min</u>	%	%	%
Below 0.5	Below 17.6	+/- 7	+/- 8	
0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	+/- 10%
1.5 to 15	53 to 529.7	+/- 5	+/- 6	
Above 15	Above 529.7	+/- 4	+/- 5	

ROT 031.1 12/19 Rev 3 This for