

## **COMPRESSOR DATA SHEET**

## In Accordance With Federal Uniform Test Method for Certain Lubricated Air Compressors Rotary Compressor: Variable Frequency Drive

MODEL DATA - FOR COMPRESSED AIR						
1 Manufacturer: Hertz Kompressoren						
Model Number: IMPETUS VSD 160	Date:	04/25/23				
Air-cooled X Water-cooled	Туре:	Screw				
X Oil-injected Oil-free	# of Stages:	2				
Rated Operating Pressure	100	psig <sup>b</sup>				
Drive Motor Nominal Rating	220	hp				
Drive Motor Nominal Efficiency	96.7	percent				
Fan Motor Nominal Rating (if applicable)	N/A	hp				
Fan Motor Nominal Efficiency	N/A	percent				
Input Power (kW)	Capacity (acfm) <sup>a,d</sup>	Specific Power (kW/100 acfm) <sup>d</sup>				
200.9 Max	1185.5	16.95				
166.7	1013.9	16.44				
136.2	839.7	16.22				
105.6	645.3	16.37				
79.0	469.8	16.81				
52.4 Min	297.3	17.64				
Total Package Input Power at Zero Flow <sup>c, d</sup>	24.3	kW				
Isentropic Efficiency	78.4	Percent				
Capaci Note: Graph is only a visual re Note: Y-Axis Scale, 10 to 35, + 5kW	ty (ACFM) presentation of the data in Section (100acfm increments if necessary al					
	MODEL DATA - FOR COM  Manufacturer: Hertz Kompressoren  Model Number: IMPETUS VSD 160  Air-cooled X Water-cooled  X Oil-injected Oil-free  Rated Operating Pressure  Drive Motor Nominal Rating  Drive Motor Nominal Efficiency  Fan Motor Nominal Efficiency  Input Power (kW)  200.9 Max  166.7  136.2  105.6  79.0  52.4 Min  Total Package Input Power at Zero Flow <sup>c, d</sup> Isentropic Efficiency  Isentropic Efficiency  15.00  15.00  10.00 200 300 400 500 600  Capaci  Note: Graph is only a visual re Note: Y-Axis Scale, 10 to 35, +5 kW.	MODEL DATA - FOR COMPRESSED AIR           Manufacturer:         Hertz Kompressoren           Model Number:         IMPETUS VSD 160         Date:           Air-cooled         X         Water-cooled         Type:           X         Oil-injected         Oil-free         # of Stages:           Rated Operating Pressure         100           Drive Motor Nominal Rating         220           Drive Motor Nominal Efficiency         96.7           Fan Motor Nominal Efficiency         N/A           Input Power (kW)         Capacity (acfm)**.d           200.9         Max         1185.5           166.7         1013.9         136.2           839.7         105.6         645.3           79.0         469.8         52.4           Min         297.3           Total Package Input Power at Zero Flow <sup>c, d</sup> 24.3           Isentropic Efficiency         78.4				

<sup>\*</sup>For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator Consult CAGI website for a list of participants in the third party verification program: <a href="www.cagi.org">www.cagi.org</a>

- a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E;
   ACFM is actual cubic feet per minute at inlet conditions.
- b. The operating pressure at which the Capacity (Item 8) and Electrical Consumption (Item 8) were measured for this data sheet.
- c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%,
- manufacturer may state "not significant" or "0" on the test report.
  d. Tolerance is specified in ISO 1217, Annex E, as shown in table below:
- NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

Member

Compressed Air & Gas Institute

Vo	olume Flow Rate		Specific Energy	
at sp	ecified conditions	Volume Flow Rate	Consumption	No Load / Zero Flow Power
m <sup>3</sup> / min	ft <sup>3</sup> / min	%	%	%
Below 0.5	Below 17.6	+/- 7	+/- 8	
0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	+/- 10%
1.5 to 15	53 to 529.7	+/- 5	+/- 6	
Above 15	Above 529.7	+/- 4	+/- 5	

ROT 031.1

12/19 Rev 3 This form was developed by the Compressed Air and Gas Institute for the use of its members participating in the PVP. CAGI has not independently verified the reported data