COMPRESSOR DATA SHEET

In Accordance With Federal Uniform Test Method for Certain Lubricated Air Compressors Rotary Compressor: Variable Frequency Drive

	MODEL DATA - FOR COM	<u> </u>	
1	Manufacturer: Hertz Kompressoren		
	Model Number: IMPETUS VSD 200	Date:	04/25/23
2	Air-cooled X Water-cooled	Type:	Screw
	X Oil-injected Oil-free	# of Stages:	2
3	Rated Operating Pressure	150	psig ^b
4	Drive Motor Nominal Rating	270	hp
5	Drive Motor Nominal Efficiency	97	percent
6	Fan Motor Nominal Rating (if applicable)	N/A	hp
7	Fan Motor Nominal Efficiency	N/A	percent
8*	Input Power (kW)	Capacity (acfm) ^{a,d}	Specific Power (kW/100 acfm) ^d
	255.5 Max	1272.3	20.08
	218.1	1090.7	19.99
0	183.3	918.9	19.94
	153.3	763.2	20.08
	119.8	587.7	20.38
	89.2 Min	405.8	21.98
9*	Total Package Input Power at Zero Flow ^{c, d}	36.6	kW
10	Isentropic Efficiency	82.4	Percent
11	Capacit Note: Graph is only a visual rep Note: Y-Axis Scale, 10 to 35, + 5kW/1	y (ACFM) resentation of the data in Sectior	

*For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator Consult CAGI website for a list of participants in the third party verification program: www.cagi.org



- a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E; ACFM is actual cubic feet per minute at inlet conditions.b. The operating pressure at which the Capacity (Item 8) and Electrical Consumption (Item 8) were measured for this data sheet.
- c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%,
- manufacturer may state "not significant" or "0" on the test report.
- d. Tolerance is specified in ISO 1217, Annex E, as shown in table below:
 - NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

Member

Volume Flow Rate			Specific Energy	
at specified conditions		Volume Flow Rate	Consumption	No Load / Zero Flow Power
$\underline{m^3 / \min}$	<u>ft³ / min</u>	%	%	%
Below 0.5	Below 17.6	+/- 7	+/- 8	+/- 10%
0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	
1.5 to 15	53 to 529.7	+/- 5	+/- 6	
Above 15	Above 529.7	+/- 4	+/- 5	