

COMPRESSOR DATA SHEET

In Accordance With Federal Uniform Test Method for Certain Lubricated Air Compressors Rotary Compressor: Variable Frequency Drive

MODEL DATA - FOR COMPRESSED AIR							
Manufacturer: Hertz Kompressoren							
odel Number:	IMPETUS VSD 200	Date:	04/25/23				
] Air-cooled	X Water-cooled	Туре:	Screw				
Oil-injected	Oil-free	# of Stages:	2				
Rated Operating Pressure		175	psig ^b				
Drive Motor Nominal Rating		270	hp				
Drive Motor Nominal Efficiency		97	percent				
Fan Motor Nominal Rating (if applicable)		N/A	hp				
Fan Motor Nominal Efficiency		N/A	percent				
Input Power (kW)		Capacity (acfm) ^{a,d}	Specific Power (kW/100 acfm) ^d				
253.0	Max	1162.9	21.76				
218.9		1012.9	21.61				
185.9		855.4	21.73				
160.8		714.7	22.50				
128.3		559.0	22.95				
99.3 Min		404.0	24.57				
Total Package Input Power at Zero Flow ^{c, d}		36.6	kW				
Isentropic Efficiency		82.3	Percent				
30.00 Z5.00 Specific Power (KW)100 ACFM) 25.00 15.00 10.00 0	Capacity Note: Graph is only a visual rep	y (ACFM) resentation of the data in Section					
		0 100 200 300 400 500 600 7 Capacity Note: Graph is only a visual rep Note: Y-Axis Scale, 10 to 35, + 5kW/1					

^{*}For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator Consult CAGI website for a list of participants in the third party verification program: www.cagi.org

- a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E;
 ACFM is actual cubic feet per minute at inlet conditions.
- b. The operating pressure at which the Capacity (Item 8) and Electrical Consumption (Item 8) were measured for this data sheet.
- c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%,
- manufacturer may state "not significant" or "0" on the test report.
 d. Tolerance is specified in ISO 1217, Annex E, as shown in table below:
- NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

Member

Compressed Air & Gas Institute

	Volume Flow Rate		Specific Energy	
	at specified conditions	Volume Flow Rate	Consumption	No Load / Zero Flow Power
m ³ / mi	<u>ft³ / min</u>	%	%	%
Below 0	5 Below 17.6	+/- 7	+/- 8	
0.5 to 1.	5 17.6 to 53	+/- 6	+/- 7	+/- 10%
1.5 to 1	5 53 to 529.7	+/- 5	+/- 6	
Above 1	5 Above 529.7	+/- 4	+/- 5	

ROT 031.1

12/19 Rev 3 This form was developed by the Compressed Air and Gas Institute for the use of its members participating in the PVP. CAGI has not independently verified the reported data