

COMPRESSOR DATA SHEET

In Accordance With Federal Uniform Test Method for Certain Lubricated Air Compressors Rotary Compressor: Variable Frequency Drive

		DEL DATA - FOR COM				
1	Manufacturer:	Hertz Kompressoren				
2	Model Number: IMPETUS VSD 250		Date:	04/25/23		
	Air-coole	X Water-cooled	Type:	Screw		
	X Oil-inject	X Oil-injected Oil-free		2		
3	Rated Operating Pres	ure	125	psig ^b		
4	Drive Motor Nomina	Rating	335	hp		
5	Drive Motor Nomina	Efficiency	97	percent		
6	Fan Motor Nominal I	ating (if applicable)	N/A	hp		
7	Fan Motor Nominal I	fficiency	N/A	percent		
	Input Power (kW)		Capacity (acfm) ^{a,d}	Specific Power (kW/100 acfm) ^d		
	299.5 Max		1697.8	17.64		
	258.0		1473.6	17.51		
8*	218.8		1247.2	17.54		
	186.4		1046.6	17.81		
	149.9		824.2	18.19		
	114.4 Min		593.1	19.29		
9*	Total Package Input I	ower at Zero Flow ^{c, d}	45.0	kW		
10	Isentropic Efficiency		85.2	Percent		
11	30.00 25.00 (RA/100 ACFM) 10.00		1000 1200 1400 160 ty (ACFM) presentation of the data in Section			
		Note: Graph is only a visual representation of the data in Section 8 Note: Y-Axis Scale, 10 to 35, + 5kW/100acfm increments if necessary above 35 X-Axis Scale, 0 to 25% over maximum capacity				

^{*}For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator Consult CAGI website for a list of participants in the third party verification program: www.cagi.org

- a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E;
 ACFM is actual cubic feet per minute at inlet conditions.
- b. The operating pressure at which the Capacity (Item 8) and Electrical Consumption (Item 8) were measured for this data sheet.
- c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%,
- manufacturer may state "not significant" or "0" on the test report.
 d. Tolerance is specified in ISO 1217, Annex E, as shown in table below:
- NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

Member

Compressed Air & Gas Institute

Volume Flow Rate			Specific Energy	
at specified conditions		Volume Flow Rate	Consumption	No Load / Zero Flow Power
m ³ / min	ft ³ / min	%	%	%
Below 0.5	Below 17.6	+/- 7	+/- 8	+/- 10%
0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	
1.5 to 15	53 to 529.7	+/- 5	+/- 6	
Above 15	Above 529.7	+/- 4	+/- 5	

ROT 031.1