COMPRESSOR DATA SHEET

In Accordance With Federal Uniform Test Method for Certain Lubricated Air Compressors Rotary Compressor: Variable Frequency Drive

	•	EL DATA - FOR COM	· ·	
1	Manufacturer:	Hertz Kompressoren		
	Model Number:	IMPETUS VSD 315	Date:	04/25/23
2	Air-cooled	X Water-cooled	Type:	Screw
	X Oil-injected	Oil-free	# of Stages:	2
3	Rated Operating Pressur	e	100	psig ^b
4	Drive Motor Nominal R	ating	425	hp
5	Drive Motor Nominal E	fficiency	96.7	percent
6	Fan Motor Nominal Rat	ing (if applicable)	N/A	hp
7	Fan Motor Nominal Effi	ciency	N/A	percent
8*	Input Power (kW)		Capacity (acfm) ^{a,d}	Specific Power (kW/100 acfm) ^d
	373.8 Max		2203.4	16.96
	313.9		1890.1	16.61
0.	259.0		1585.9	16.33
	197.2		1231.4	16.01
	147.2		925.0	15.91
	101.0 Min		591.3	17.09
9*	Total Package Input Pov	ver at Zero Flow ^{c, d}	73.0	kW
10	Isentropic Efficiency		78.4	Percent
11	30.00 25.00 25.00 20.00 15.00 10.00 0	Note: Graph is only a visual rep Note: Y-Axis Scale, 10 to 35, + 5kW/1		8

*For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator Consult CAGI website for a list of participants in the third party verification program: www.cagi.org



a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E; ACFM is actual cubic feet per minute at inlet conditions.
b. The operating pressure at which the Capacity (Item 8) and Electrical Consumption (Item 8) were measured for this data sheet.

c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%,

manufacturer may state "not significant" or "0" on the test report.

d. Tolerance is specified in ISO 1217, Annex E, as shown in table below:

NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

Member

Vo	lume Flow Rate		Specific Energy	
at sp	ecified conditions	Volume Flow Rate	Consumption	No Load / Zero Flow Power
$\underline{m^3 / \min}$	<u>ft³ / min</u>	%	%	%
Below 0.5	Below 17.6	+/- 7	+/- 8	
0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	+/- 10%
1.5 to 15	53 to 529.7	+/- 5	+/- 6	
Above 15	Above 529.7	+/- 4	+/- 5	