

## **COMPRESSOR DATA SHEET**

## In Accordance With Federal Uniform Test Method for Certain Lubricated Air Compressors Rotary Compressor: Variable Frequency Drive

MODEL DATA - FOR COMPRESSED AIR									
1	Manufacturer: Hertz Kompressoren								
	Model Number:	IMPETUS VSD 90	Date	04/25/23					
2	Air-co	ooled X Water-cooled	Type:	Screw					
	X Oil-in	jected Oil-free	# of Stages:						
3	Rated Operating I	Pressure	175	psig <sup>b</sup>					
4	Drive Motor Non	ninal Rating	125	hp					
5	Drive Motor Non	ninal Efficiency	96.5	percent					
6	Fan Motor Nomir	nal Rating (if applicable)	N/A	hp					
7	Fan Motor Nomir	al Efficiency	N/A	percent					
	Input Power (kW)		Capacity (acfm) <sup>a,d</sup>	Specific Power (kW/100 acfm) <sup>d</sup>					
	105.5 Max		481.4	21.92					
0.*	91.7		418.6	21.91					
8*	80.9		362.1	22.33					
	68.5		295.3	23.20					
	58.7		234.0	25.09					
	47.3 Min		in 171.3	27.63					
9*	Total Package Inp	out Power at Zero Flow <sup>c, d</sup>	14.1	kW					
10	Isentropic Efficier	ıcy	81.7	Percent					
11	Specific Power (kW/100 ACFM)	Note: Graph is only a visu Note: Y-Axis Scale, 10 to 35, +	300 400 500  pacity (ACFM)  all representation of the data in Seciew/100acfm increments if necessar						
		Note: Graph is only a visu Note: Y-Axis Scale, 10 to 35, +	pacity (ACFM) Il representation of the data in Sec	ction 8					

\*For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator Consult CAGI website for a list of participants in the third party verification program: <a href="www.cagi.org">www.cagi.org</a>

- a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E;
   ACFM is actual cubic feet per minute at inlet conditions.
- b. The operating pressure at which the Capacity (Item 8) and Electrical Consumption (Item 8) were measured for this data sheet.
- c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.
- d. Tolerance is specified in ISO 1217, Annex E, as shown in table below:

NOTE: The terms "power" and "energy" are synonymous for purposes of this document.



Volume Flow Rate			Specific Energy		
at specified conditions		Volume Flow Rate	Consumption	No Load / Zero Flow Power	
	$\underline{\mathbf{m}^3 / \mathbf{min}}$	ft <sup>3</sup> / min	%	%	%
	Below 0.5	Below 17.6	+/- 7	+/- 8	
	0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	+/- 10%
	1.5 to 15	53 to 529.7	+/- 5	+/- 6	+/- 10%

Member

Above 529.7