

5-7.5-10  
HP

175  
psi

19-38  
cfm



Learn more

Oil Injected, Silent Air  
**Reciprocating Air Compressors**

### Advantages

- Patented silent air system reduces the decibels by more than 50% by adding 4 layers of air filtration.
- The magnetic starter provides a safe start method along with the overload protection when starting.  
(7.5 HP and up models)
- Easy two-turn design of belt tension adjuster reduces vibration and extends belt life.
- It delivers up to 38 CFM from single phase 10 HP models.
- Continuous mode functionality eliminates wear and tear on your magnetic contactor for workloads over 50%.

### General Features

- Extended life time thanks to patented pressure lubricated pump
- No daily maintenance with 110-volt dual timer controlled auto tank drain
- Powder coated ASME certified tanks with 200 PSI rating
- B-style belts to ensure smooth operation
- Top quality pressure switches
- 100% brass valves
- 16G steel with premium grade expanded metal belt guards
- Low in take noise by channeling the in take air through a series of baffle plates

Model	Pressure		Intake Capacity		Motor	Voltage	Tank Volume	Dimensions	Weight
	bar	psi	L/min.	cfm	kW/HP	V/ph/hz	Gal	Length x Width x Height	lbs
HPC 5 E	12.1	175	538	19	4 / 5	230/1/60	80	34" x 42" x 75"	620
						230&460/3/460			
HPC 7.5 E	12.1	175	878	31	5.5 / 7.5	230/1/60	80	38" x 42" x 73"	743
						230&460/3/460			
HPC 10 E	12.1	175	1076	38	7.5 / 10	230/1/60	120	41" x 43" x 79"	1020
						230&460/3/460			