

100-10000  
L

Vertical

10-40  
barAIR  
RECEIVERS

Air tanks are used for storage in compressed air systems. They prevent pressure fluctuations in the system and eliminate inefficiencies especially in fix speed compressor applications.

 **Advantages**

- They allow the system to respond quickly to high and sudden consumption
- A key component of compressed air systems
- Storage function
- Reduces system pressure fluctuations
- Increases efficiency
- Galvanized and stainless steel options
- Energy saving
- Highly durable with a long service life

Model	Volume	Pressure	Configuration	Dimensions (mm)		Connection Inlet / Outlet
	L	bar		Diameter	Height	
HAR 100	100	10	VERTICAL	324	1564	G 1"
		15	VERTICAL	324	1564	G 1"
HAR 200	200	10	VERTICAL	450	1618	G 1"
		15	VERTICAL	450	1618	G 1"
HAR 300	300	10	VERTICAL	450	1918	G ¾"
		16,5	VERTICAL	500	1960	G 1"
		40	VERTICAL	450	2012	G 1"
HAR 500	500	10	VERTICAL	642	1980	G 1"
		17	VERTICAL	642	2115	G 1"
		40	VERTICAL	642	2083	G 1 ¼"
HAR 900	900	10	VERTICAL	800	2120	G 1 ½"
HAR 1000	1000	10	VERTICAL	850	2120	G 1 ½"
		17	VERTICAL	850	2292	G 1 ½"
		40	VERTICAL	850	2120	G 1 ½"
HAR 1800	1800	10	VERTICAL	1150	2150	G 2"
		15	VERTICAL	1150	2150	G 2"
HAR 2000	2000	10	VERTICAL	1080	2566	G 2"
		15	VERTICAL	1080	2566	G 2"
		15	VERTICAL	1150	2240	G 2"
HAR 3000	3000	10	VERTICAL	1400	2370	G 2 ½"
		15	VERTICAL	1400	2370	G 2 ½"
HAR 4000	4000	10	VERTICAL	1400	3120	G 3"
		15	VERTICAL	1400	3120	G 3"
HAR 5000	5000	10	VERTICAL	1400	3870	G 3"
		15	VERTICAL	1400	3870	G 3"
HAR 6000	6000	10	VERTICAL	1500	3930	G 3"
		15	VERTICAL	1500	3930	G 3"
HAR 8000	8000	10	VERTICAL	1750	4040	DN100
		15	VERTICAL	1750	4040	DN100
HAR 10000	10000	10	VERTICAL	1900	4100	DN100
		15	VERTICAL	1900	4100	DN100